

## SF6 GAS LOAD BREAK SWITCH (REMOTE CONTROLLED SWITCH)



SF6 Gas Load Break Switch

Specification	Type	GK-GS2406	GK-GS3606
Rated Voltage	kV	24	36
Continuous Current	A	630	400
BIL	kV	150	170
Frequency	Hz	50 / 60	
Rated Short time Current (1s)	kA	12.5	10
Rated Making Current (Peak)	kV	32.5	25
Rated Power Frequency withstand Voltage			
Dry (1min)	kV	60	70
Wet (10s)	kV	60	
Number of Operation			
Mechanical	Operations	2,000	
Load Switching	Operations	400	
Total Weight	kg	160	185
Price	Manual	300,000.00	350,000.00
	Electrical	350,000.00	400,000.00

## sf6 gas or solid Dielectric Insulated recloser

Specification		
Rated Voltage	kV	25.8
Continuous Current	A	630
Frequency	Hz	50 / 60
Rated Symmetrical interrupting current	kA	12.5 / 16
Short time withstand current, 1 sec	kA	12.5 / 16
Making current	kA	32.5 / 41.6
Cable charging interrupting current	A	5
Basic impulse withstand voltage	kV	150
Power frequency withstand voltage, dry	kV	60
Control voltage	AC / DC	AC 220/110V, DC 24V
Mechanical endurance	times	10,000
Price		900,000.00



SF6 Type

Solid Type