

SF6 GAS LOAD BREAK SWITCH (REMOTE CONTROLLED SWITCH)



SF6 Gas Load Break Switch

| Specification | Type | GK-GS2406 | GK-GS3606 |
|---|------------|------------|------------|
| Rated Voltage | kV | 24 | 36 |
| Continuous Current | A | 630 | 400 |
| BIL | kV | 150 | 170 |
| Frequency | Hz | 50 / 60 | |
| Rated Short time Current (1s) | kA | 12.5 | 10 |
| Rated Making Current (Peak) | kV | 32.5 | 25 |
| Rated Power Frequency withstand Voltage | | | |
| Dry (1min) | kV | 60 | 70 |
| Wet (10s) | kV | 60 | |
| Number of Operation | | | |
| Mechanical | Operations | 2,000 | |
| Load Switching | Operations | 400 | |
| Total Weight | kg | 160 | 185 |
| Price | Manual | 300,000.00 | 350,000.00 |
| | Electrical | 350,000.00 | 400,000.00 |

sf6 gas or solid Dielectric Insulated recloser

| Specification | | |
|--|---------|---------------------|
| Rated Voltage | kV | 25.8 |
| Continuous Current | A | 630 |
| Frequency | Hz | 50 / 60 |
| Rated Symmetrical interrupting current | kA | 12.5 / 16 |
| Short time withstand current, 1 sec | kA | 12.5 / 16 |
| Making current | kA | 32.5 / 41.6 |
| Cable charging interrupting current | A | 5 |
| Basic impulse withstand voltage | kV | 150 |
| Power frequency withstand voltage, dry | kV | 60 |
| Control voltage | AC / DC | AC 220/110V, DC 24V |
| Mechanical endurance | times | 10,000 |
| Price | | 900,000.00 |



SF6 Type

Solid Type